SINGLE-ENDED BEAM **RL32218S-HE**

Stainless Steel, Hermetically Sealed, NTEP Certified 1:5,000 Class III Multiple Cell, IP69K

Interchangeable Products RICE LAKE WEIGHING SYSTEMS **RL35082HE** page 142 VPG SENSORTRONICS® **65083S**......page 323 Weigh Module Available RICE LAKE WEIGHING SYSTEMS **RL50210TA**.....page 52

RL1800 Series..... page 62



Specifications

Full Scale Output:

 $2.0\,\text{mV/V}$ $\pm 0.05\%$ current matched

RICE LAKE WEIGHING SYSTEMS

Output Resistance:

350 (± 3) ohm

Input Resistance:

400 (± 20) ohm

Material/Finish:

Stainless steel

Temperature:

Compensated range: 14° F to 104° F/-10° C to 40° C Operating range: -40° F to 150° F/-40° C to 65° C

Seal Type:

Hermetically sealed, IP69K

Safe Overload:

150% full scale

Rated Excitation:

5-10 VDC (15 V maximum)

Combined Error:

0.017% full scale

Insulation Resistance:

>5,000 megohms

Cable Length:

20ft (6.1 m) PTFE

Cable Color Code:

Rea+	Excitatio
Black	Excitatio
Green+	Signal
White	Signal

Warranty:

Two-year limited warranty

Approvals:





Dimensions

Picture is a representation of actual product

Rated Capacity	A	В	C	D	E	F	G	Н	I	J	K	L	M	N
lb/in														
1,000-4,000	1.24	0.59	0.96	2.20	1.24	5.12	0.53	0.70	1/2- 20 UNF	3.00	1.00	0.62	0.25	0.13
5,000-10,000	1.88	-	1.45	2.99	1.63	6.75	0.80	0.70	3/4- 16 UNF	3.75	1.50	0.75	-	-
kg/mm														
453.6-1,814.4	31.5	15	24.6	56	31.5	130	13.5	18	1/2- 20 UNF	76.2	25.4	15.8	6.5	3.5
2,268-4,535.9	48	-	37	76	41.5	171.5	20.5	18	3/4- 16 UNF	95.2	38.1	19	-	-

Order Information

Load Rating		Part#	Est. Weight	Price
1,000 lb	453.6 kg	191634	3 lb	Consult
2,500 lb	1,134 kg	191635	3 lb	Consult
4,000 lb	1,814.4 kg	191636	3 lb	Consult
5,000 lb	2,268 kg	191637	5 lb	Consult
10,000 lb	4,535.9 kg	191638	5 lb	Consult

